



SAFETY DATA SHEET

US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Issuing Date 18-Feb-2022 Revision Date 18-Feb-2022 Revision Number 1

1. Identification

Product identifier

Product Name AMSOIL Silicone Spray

Other means of identification

Product Code(s) ALSSP

UN/ID no UN1950

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Lubricant

Restrictions on use No specific uses advised against are identified

Details of the supplier of the safety data sheet

Initial supplier identifier

AMSOIL INC.
Bay Adelaide Centre, East
Tower
22 Adelaide St. W
Toronto, ON, Canada M5H 4E3
T:+1 877-822-5172

Manufacturer Address

AMSOIL INC.
One AMSOIL Center
Superior, WI 54880, USA
T: +1 715-392-7101

E-mail

compliance@amsoil.com

Emergency telephone number

Emergency telephone CHEMTREC: Within USA and Canada: 1-800-424-9300
Outside the USA and Canada: +1 703-741-5970
(collect calls accepted) 24/7

2. Hazard(s) identification

Classification

Skin corrosion/irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration hazard	Category 1
Flammable aerosols	Category 1

Label elements

Danger

Hazard statements
Extremely flammable aerosol.
Causes skin irritation.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.
Toxic to aquatic life.
Harmful to aquatic life with long lasting effects.
May be fatal if swallowed and enters airways.



Precautionary Statements - Prevention
Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection and face protection. Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust, fume, gas, mist, vapors and spray. Use only outdoors or in a well-ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Precautionary Statements - Response
IF exposed or concerned: Get medical advice/attention. Specific treatment (see supplemental first aid instructions on this label).

Skin
IF ON SKIN: Wash with plenty of water and soap. If skin irritation occurs: Get medical advice and attention. Take off contaminated clothing and wash it before reuse.

Inhalation
IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion
IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

Precautionary Statements - Storage
Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary Statements - Disposal
Dispose of contents and container to an approved waste disposal plant.

Other information
May be harmful in contact with skin. Toxic to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance
Not applicable.

Mixture

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
1,1-difluoroethane	75-37-6	30 -< 60	-	-
Hydrogenated base oil	64742-49-0	25 -< 50	-	-
Hexane	110-54-3	10 -< 25	-	-

Polydimethylsiloxane	63148-62-9	1 -<5	-	-
----------------------	------------	-------	---	---

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Chemical Additions

The classification as a carcinogen does not apply as it can be shown that the substance(s) contain(s) less than 3% DMSO extract as measured by IP 346.

4. First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Inhalation	Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical advice/attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
----------	---

Indication of any immediate medical attention and special treatment needed

Note to physicians	Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.
--------------------	---

5. Fire-fighting measures

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray. Use extinguishing agent suitable for type of surrounding fire. Use water spray to cool fire-exposed containers.
Unsuitable extinguishing media	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.
Specific hazards arising from the chemical	Risk of ignition. Vapors may travel to source of ignition and flash back. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in



accordance with local regulations. Containers can burst or explode when heated, due to excessive pressure build-up. Damaged cylinders should be handled only by specialists. Containers may explode when heated.

Hazardous combustion products Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

Explosion data
Sensitivity to mechanical impact None.
Sensitivity to static discharge Yes.

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor. Prevent materials or runoff from entering drains, sewers, streams, ground water or bodies of water.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Prevent product from entering drains.

Reference to other sections For additional information see: Section 8: Exposure controls/personal protection; Section 12: Ecological information; Section 13: Disposal considerations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapors or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Avoid contact with used product. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near



combustible materials. Keep in an area equipped with sprinklers. Do not reuse empty containers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep at a temperature not exceeding 50 °C. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Control parameters

Exposure Limits Under conditions which may generate mists, the following exposure limits are recommended: Long-term exposure limit (8-hour TWA): 5 mg/m³. Short-term exposure limit (15-minute): 10 mg/m³.

Chemical name	ACGIH TLV		OSHA PEL	NIOSH
Hexane 110-54-3	TWA: 50 ppm S*		TWA: 500 ppm TWA: 1800 mg/m³ (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m³	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m³
Chemical name	Alberta	British Columbia	Ontario	Quebec
Hexane 110-54-3	TWA: 50 ppm TWA: 176 mg/m³ Skin	TWA: 20 ppm Skin	TWA: 50 ppm Skin	TWA: 50 ppm TWA: 176 mg/m³ Skin

Biological occupational exposure limits

Chemical name	ACGIH
Hexane 110-54-3	0.5 mg/L - urine (2,5-Hexanedione without hydrolysis) - end of shift

Appropriate engineering controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Face protection shield.

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. Consult with an industrial hygienist to determine the appropriate respiratory protection for your specific use of this material.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance

Physical state Liquid

Color Clear white

Odor Mild solvent



Odor threshold	No information available	
<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH		No data available
Melting point / freezing point		No data available
Initial boiling point and boiling range		No data available
Flash point	104 °C / 219.2 °F	Estimated
Evaporation rate		No data available
Flammability		No data available
Flammability Limit in Air		
Upper flammability or explosive limits	16.9 % (V)	Estimated
Lower flammability or explosive limits	3.9 % (V)	Estimated
Vapor pressure	3,240 - 3,930 hPa (20 °C) 7,239 - 7,928 hPa (54 °C)	No data available
Vapor density		No data available
Relative density		No data available
Water solubility		No data available
Solubility(ies)		No data available
Partition coefficient		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available
<u>Other information</u>		
Explosive properties	No information available.	
Oxidizing properties	No information available.	
Softening point	No information available	
Molecular weight	No information available	
VOC Content (%)	No information available	
Liquid Density	No information available	
Bulk density	No information available	

10. Stability and reactivity

Reactivity	None under normal use conditions.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong acids. Strong bases. Strong oxidizing agents.
Hazardous decomposition products	Thermal decomposition can lead to release of irritating and toxic gases and vapors Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
------------	--



Eye contact	Specific test data for the substance or mixture is not available. May cause irritation.
Skin contact	Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
----------	---

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document:

ATEmix (oral)	10,010.000 mg/kg
ATEmix (dermal)	4,142.40 mg/kg

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
1,1-difluoroethane	-	-	= 437500 ppm (Rat) 4 h
Hydrogenated base oil	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 73680 ppm (Rat) 4 h
Hexane	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
Polydimethylsiloxane	> 24 g/kg (Rat)	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Causes skin irritation.
Serious eye damage/eye irritation	No information available.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	The supplier declares that it can be shown that the substance(s) contain less than 3% DMSO extract as measured by IP 346.
Reproductive toxicity	Contains a known or suspected reproductive toxin. Classification based on data available for ingredients. Suspected of damaging fertility or the unborn child.
STOT - single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity	Toxic to aquatic life. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.
-------------	--



Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Hydrogenated base oil 64742-49-0	-	LC50: =8.41mg/L (96h, Oncorhynchus mykiss)	-	-
Hexane 110-54-3	-	LC50: 2.1 - 2.98mg/L (96h, Pimephales promelas)	-	-

Persistence and degradability	No information available.
Bioaccumulation	No information available.
Mobility in soil	No information available.
Other adverse effects	No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products	Should not be released into the environment, Dispose of in accordance with local regulations, Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Do not reuse empty containers.
California waste information	This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. Transport information

DOT

UN/ID no	UN1950
Proper shipping name	AEROSOLS
Transport hazard class(es)	2.1
Reportable Quantity (RQ)	(Hexane: RQ (kg)= 2270.00) Hexane: RQ (lb)= 5000.00
Reportable quantity kg (calculated)	Hexane: RQ (kg)= 9080.00
Reportable quantity lbs. (calculated)	Hexane: RQ (lb)= 20000.00
Special Provisions	N82
DOT Marine Pollutant	P
Marine pollutant	Hexane
Description	UN1950, AEROSOLS, 2.1, Marine pollutant (Hexane)
Emergency Response Guide Number	126

TDG

UN/ID no	UN1950
Proper shipping name	AEROSOLS
Hazard class	2.1
Special Provisions	80, 107
Marine pollutant	Hydrogenated base oil, Hexane.
Description	UN1950, Aerosols, 2.1

IATA

UN number or ID number	UN1950
UN proper shipping name	Aerosols, flammable



Transport hazard class(es)	2.1
ERG Code	10L
Special Provisions	A145, A167, A802
Description	UN1950, Aerosols, flammable, 2.1

IMDG

UN number or ID number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	2.1
EmS-No	F-D, S-U
Special Provisions	63,190, 277, 327, 344, 381, 959
Marine pollutant	P
Marine pollutant	Hydrogenated base oil
Description	UN1950, AEROSOLS (Hydrogenated base oil), 2.1, Marine pollutant

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

Contact supplier for inventory compliance status

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
Hexane - 110-54-3	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Hexane 110-54-3	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65



This product contains the following Proposition 65 chemicals:.

Chemical name	California Proposition 65
Hexane - 110-54-3	Male Reproductive
Benzene - 71-43-2	Carcinogen Developmental Male Reproductive

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
1,1-difluoroethane 75-37-6	X	X	-
Hexane 110-54-3	X	X	X
Benzene 71-43-2	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend	Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION		
TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

Key literature references and sources for data used to compile the SDS

U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGL(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
Japan GHS Classification
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Issuing Date	18-Feb-2022
Revision Date	18-Feb-2022
Revision Note	Initial Release.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage,



transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

